

ViaLite outdoor enclosures provide a cost-effective housing solution in a variety of sizes that can be used indoors or outdoors, and in environmentally harsh conditions. The range comprises of the Satcom6, as well as the ODE series which includes the ODE-A4 and ODE-MINI.

	ODE-MINI	ODE-A4	Satcom6	ODE-B3U	ODE-C	ODE-D	ODE-D+
Dual PSUs	✓	✓	✓	✓	✓	✓	✓
External Dimensions (mm)	220 x 155 x 95	295 x 217.5 x 74	380 x 300 x 210	600 x 600 x 220	612 x 610 x 640	1550 x 850 x 725	1550 x 850 x 725
AC & DC Input options	AC & DC	AC & DC	AC & DC	N/A	N/A	N/A	N/A
Blue Modules	2	4	✗	✗	✗	✗	✗
Yellow Modules	✗	✗	6	✗	✗	✗	✗
Purple Modules	1	1	✗	✗	✗	✗	✗
LNA/BUC Power Feed	✓	✓	✓	✗	✗	✗	✗
Max. number RFoF modules/channels	2	4	6	16*	104	214	214
Site Controller	✓	✓	✗	✗	✗	✗	✗
HRC-3 SNMP	✗	✗	✓	✓	✓	✓	✓
Space for Splitters/Combiners/LNA	✓	✓	✓	✓	✓	✓	✓
Split Gland option	✗	✓	✓	✓	✗	✗	✗
Quick Release Connectors	✓	✓	✓	✗	✗	✗	✗
19" Chassis Mounting option	✗	✗	✗	✓	✓	✓	✓
Wall Mount	✓	✓	✓	✓	✗	✗	✗
Pole Mount	✓	✓	✓	✗	✗	✗	✗
IP Rating	IP65	IP65	IP66	IP66	IP55	IP55	IP55
Heater option	✗	✓	✓	✓	✓	✓	✓
Solar Shield	✗	✓	✓	✓	✓	✓	✓
Air Conditioning	✗	✗	✗	✗	✗	✗	✓
Humidity Vented	✗	✗	✗	✓	✓	✓	✓
5 Year Warranty	✓	✓	✓	✓	✓	✓	✓
Ambient Operating Temperature	-20°C to +60°C	-40°C to +60°C	-40°C to +60°C	-40°C to +60°C	-40°C to +60°C	-40°C to +60°C	-40°C to +60°C

*20 with optional fan assembly