

ViaLite outdoor enclosures provide a cost-effective housing solution in a variety of sizes that can be used indoors or outdoors, and in environmentally harsh conditions. The ODE range includes the compact ODE-A4 and ODE-MINI, along with larger enclosures for rack-based equipment.

	ODE-MINI	ODE-A4	ODE-B3U	ODE-D	ODE-D+
Dual PSUs	✓	✓	✓	✓	✓
External Dimensions (mm)	220 x 155 x 95	295 x 217.5 x 74	600 x 600 x 220	1550 x 850 x 725	1550 x 850 x 725
AC & DC Input options	AC & DC	AC & DC	N/A	N/A	N/A
Blue Modules	2	4	✗	✗	✗
Yellow Modules	✗	✗	✗	✗	✗
Purple Modules	1	1	✗	✗	✗
LNA/BUC Power Feed	✓	✓	✗	✗	✗
Max. number RFoF modules/channels	2	4	20	214	214
Site Controller	✓	✓	✗	✗	✗
SNMP Monitoring and Control	✗	✗	✓	✓	✓
Space for Splitters/Combiners/LNA	✓	✓	✓	✓	✓
Split Gland option	✗	✓	✓	✗	✗
Quick Release Connectors	✓	✓	✗	✗	✗
19" Chassis Mounting option	✗	✗	✓	✓	✓
Wall Mount	✓	✓	✓	✗	✗
Pole Mount	✓	✓	✗	✗	✗
IP Rating	IP65	IP65	IP66	IP55	IP55
Heater option	✗	✓	✓	✓	✓
Solar Shield	✗	✓	✓	✓	✓
Air Conditioning	✗	✗	✗	✗	✓
Humidity Vented	✗	✗	✓	✓	✓
5 Year Warranty	✓	✓	✓	✓	✓
Ambient Operating Temperature	-20°C to +60°C	-40°C to +60°C	-40°C to +60°C	-40°C to +60°C	-40°C to +60°C